

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

**Product Description:** Hydrogen chloride, 1N solution in diethyl ether  
**Cat No. :** 368460000; 368461000; 368468000

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

<b>Recommended Use</b>	Laboratory chemicals.
<b>Sector of use</b>	SU3 - Industrial uses: Uses of substances as such or in preparations at industrial sites
<b>Product category</b>	PC21 - Laboratory chemicals
<b>Process categories</b>	PROC15 - Use as a laboratory reagent
<b>Environmental release category</b>	ERC6a - Industrial use resulting in manufacture of another substance (use of intermediates)
<b>Uses advised against</b>	No Information available

### 1.3. Details of the supplier of the safety data sheet

#### Company

**UK entity/business name**  
Fisher Scientific UK  
Bishop Meadow Road,  
Loughborough, Leicestershire LE11 5RG, United Kingdom

**EU entity/business name**  
Thermo Fisher Scientific  
Janssen Pharmaceuticaan 3a, 2440 Geel, Belgium

**E-mail address** begel.sdsdesk@thermofisher.com

### 1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11  
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99  
**CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

**CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567**

#### Physical hazards

Flammable liquids

Category 1 (H224)

#### Health hazards

# SAFETY DATA SHEET

Hydrogen chloride, 1N solution in diethyl ether

Revision Date 09-Feb-2024

Acute oral toxicity  
Skin Corrosion/Irritation  
Serious Eye Damage/Eye Irritation  
Specific target organ toxicity - (single exposure)

Category 4 (H302)  
Category 1 A (H314)  
Category 1 (H318)  
Category 3 (H336)

## **Environmental hazards**

Based on available data, the classification criteria are not met

Full text of Hazard Statements: see section 16

## **2.2. Label elements**



Signal Word

Danger

## **Hazard Statements**

H224 - Extremely flammable liquid and vapor  
H302 - Harmful if swallowed  
H314 - Causes severe skin burns and eye damage  
H336 - May cause drowsiness or dizziness  
EUH019 - May form explosive peroxides  
EUH066 - Repeated exposure may cause skin dryness or cracking

## **Precautionary Statements**

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
P260 - Do not breathe dust/fume/gas/mist/vapors/spray  
P264 - Wash face, hands and any exposed skin thoroughly after handling  
P280 - Wear protective gloves/protective clothing/eye protection/face protection  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
P310 - Immediately call a POISON CENTER or doctor/physician

## **2.3. Other hazards**

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB)

Toxic to terrestrial vertebrates

This product does not contain any known or suspected endocrine disruptors

## **SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

### **3.2. Mixtures**

Component	CAS No	EC No	Weight %	CLP Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567
Ethyl ether	60-29-7	EEC No. 200-467-2	90-95	Flam. Liq. 1 (H224) Acute Tox. 4 (H302) STOT SE 3 (H336) (EUH019)

# SAFETY DATA SHEET

Hydrogen chloride, 1N solution in diethyl ether

Revision Date 09-Feb-2024

				(EUH066)
Hydrogen chloride	7647-01-0	231-595-7	5-10	Skin Corr. 1A (H314) Eye Dam. 1 (H318) Acute Tox. 3 (H331) EUH071

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Hydrogen chloride	-	-	-

Full text of Hazard Statements: see section 16

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

<b>Eye Contact</b>	Immediate medical attention is required. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
<b>Skin Contact</b>	Immediate medical attention is required. Wash off immediately with plenty of water for at least 15 minutes.
<b>Ingestion</b>	Do NOT induce vomiting. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.
<b>Inhalation</b>	Remove to fresh air. If breathing is difficult, give oxygen. Immediate medical attention is required. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.
<b>Self-Protection of the First Aider</b>	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

### 4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Causes burns by all exposure routes. . Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting: Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated: Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation

### 4.3. Indication of any immediate medical attention and special treatment needed

**Notes to Physician** Treat symptomatically.

## SECTION 5: FIREFIGHTING MEASURES

### 5.1. Extinguishing media

#### **Suitable Extinguishing Media**

Carbon dioxide (CO<sub>2</sub>). Dry chemical. Water mist may be used to cool closed containers. Water mist may be used to cool closed containers.

#### **Extinguishing media which must not be used for safety reasons**

No information available.

### 5.2. Special hazards arising from the substance or mixture

Extremely flammable. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

# SAFETY DATA SHEET

Hydrogen chloride, 1N solution in diethyl ether

Revision Date 09-Feb-2024

Containers may explode when heated. May re-ignite after fire is extinguished. Thermal decomposition can lead to release of irritating gases and vapors. May form explosive peroxides. Corrosive material. Vapors may form explosive mixtures with air.

## Hazardous Combustion Products

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>), Hydrogen chloride gas.

### 5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges. Pay attention to flashback. Avoid contact with skin, eyes and inhalation of vapors.

### 6.2. Environmental precautions

See Section 12 for additional Ecological Information.

### 6.3. Methods and material for containment and cleaning up

Remove all sources of ignition. Provide adequate ventilation. Use spark-proof tools and explosion-proof equipment. Soak up with inert absorbent material. Keep combustibles (wood, paper, oil, etc) away from spilled material. Keep in suitable, closed containers for disposal.

### 6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for safe handling

Use only under a chemical fume hood. Wear personal protective equipment/face protection. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment. Do not get in eyes, on skin, or on clothing. Do not breathe mist/vapors/spray. Use caution when opening. Contents may develop pressure upon prolonged storage. If peroxide formation is suspected, do not open or move container. Protect from moisture. Protect from light. Do not ingest. If swallowed then seek immediate medical assistance. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges.

### **Hygiene Measures**

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

### 7.2. Conditions for safe storage, including any incompatibilities

Flammables area. Keep away from heat, sparks and flame. Protect from direct sunlight. Keep under nitrogen. May form explosive peroxides on prolonged storage. Containers should be dated when opened and tested periodically for the presence of peroxides. Should crystals form in a peroxidizable liquid, peroxidation may have occurred and the product should be considered extremely dangerous. In this instance, the container should only be opened remotely by professionals. Do not store in metal containers. Keep only in the original container. Keep container tightly closed in a dry and well-ventilated place. Refrigerator/flammables.

**Technical Rules for Hazardous Substances (TRGS) 510**  
**Storage Class (LGK) (Germany)**

Class 3

# SAFETY DATA SHEET

Hydrogen chloride, 1N solution in diethyl ether

Revision Date 09-Feb-2024

### 7.3. Specific end use(s)

Use in laboratories

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

#### Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

Component	The United Kingdom	European Union	Ireland
Ethyl ether	STEL: 200 ppm 15 min STEL: 620 mg/m <sup>3</sup> 15 min TWA: 100 ppm 8 hr TWA: 310 mg/m <sup>3</sup> 8 hr	TWA: 100 ppm (8h) TWA: 308 mg/m <sup>3</sup> (8h) STEL: 200 ppm (15min) STEL: 616 mg/m <sup>3</sup> (15min)	TWA: 100 ppm 8 hr. TWA: 308 mg/m <sup>3</sup> 8 hr. STEL: 200 ppm 15 min STEL: 616 mg/m <sup>3</sup> 15 min
Hydrogen chloride	STEL: 5 ppm 15 min STEL: 8 mg/m <sup>3</sup> 15 min TWA: 1 ppm 8 hr TWA: 2 mg/m <sup>3</sup> 8 hr	TWA: 5 ppm (8h) TWA: 8 mg/m <sup>3</sup> (8h) STEL: 10 ppm (15min) STEL: 15 mg/m <sup>3</sup> (15min)	TWA: 8 mg/m <sup>3</sup> 8 hr. F TWA: 5 ppm 8 hr. STEL: 10 ppm 15 min STEL: 15 mg/m <sup>3</sup> 15 min

#### Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

#### Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Ethyl ether 60-29-7 ( 90-95 )				DNEL = 44mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Ethyl ether 60-29-7 ( 90-95 )		DNEL = 616mg/m <sup>3</sup>		DNEL = 308mg/m <sup>3</sup>
Hydrogen chloride 7647-01-0 ( 5-10 )	DNEL = 15mg/m <sup>3</sup>		DNEL = 8mg/m <sup>3</sup>	

#### Predicted No Effect Concentration (PNEC)

See values below.

Component	Fresh water	Fresh water sediment	Water Intermittent	Microorganisms in sewage treatment	Soil (Agriculture)
Ethyl ether 60-29-7 ( 90-95 )	PNEC = 2mg/L	PNEC = 9.14mg/kg sediment dw	PNEC = 1.65mg/L	PNEC = 4.2mg/L	PNEC = 0.66mg/kg soil dw

Component	Marine water	Marine water sediment	Marine water intermittent	Food chain	Air
Ethyl ether 60-29-7 ( 90-95 )	PNEC = 0.2mg/L	PNEC = 0.914mg/kg sediment dw			

# SAFETY DATA SHEET

Hydrogen chloride, 1N solution in diethyl ether

Revision Date 09-Feb-2024

## 8.2. Exposure controls

### Engineering Measures

Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting equipment. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

### Personal protective equipment

#### Eye Protection

Goggles (European standard - EN 166)

#### Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Nitrile rubber	See manufacturers recommendations	-	EN 374	(minimum requirement)
Neoprene				
Natural rubber				
PVC				

#### Skin and body protection

Wear appropriate protective gloves and clothing to prevent skin exposure.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves.

(Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatibility, Dexterity, Operational conditions, User susceptibility, e.g.

sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

#### Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

#### Large scale/emergency use

Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced

**Recommended Filter type:** Organic gases and vapours filter Type A Brown conforming to EN14387

#### Small scale/Laboratory use

Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

**Recommended half mask:-** Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141

When RPE is used a face piece Fit Test should be conducted

**Environmental exposure controls** No information available.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

#### Physical State

Liquid

#### Appearance

Colorless

#### Odor

No information available

#### Odor Threshold

No data available

#### Melting Point/Range

No data available

#### Softening Point

No data available

#### Boiling Point/Range

No information available

#### Flammability (liquid)

Extremely flammable

On basis of test data

#### Flammability (solid,gas)

Not applicable

Liquid

#### Explosion Limits

No data available

# SAFETY DATA SHEET

Hydrogen chloride, 1N solution in diethyl ether

Revision Date 09-Feb-2024

<b>Flash Point</b>	-40 °C / -40 °F	<b>Method</b> - No information available
<b>Autoignition Temperature</b>	No data available	
<b>Decomposition Temperature</b>	No data available	
<b>pH</b>	No information available	
<b>Viscosity</b>	No data available	
<b>Water Solubility</b>	Soluble	
<b>Solubility in other solvents</b>	No information available	
<b>Partition Coefficient (n-octanol/water)</b>		
<b>Component</b>	<b>log Pow</b>	
Ethyl ether	0.82	
<b>Vapor Pressure</b>	No data available	
<b>Density / Specific Gravity</b>	0.731-0.747	
<b>Bulk Density</b>	Not applicable	Liquid
<b>Vapor Density</b>	No data available	(Air = 1.0)
<b>Particle characteristics</b>	Not applicable (liquid)	

## 9.2. Other information

**Explosive Properties** Vapors may form explosive mixtures with air

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

None known, based on information available

### 10.2. Chemical stability

May form explosive peroxides. Reacts with air to form peroxides. Hygroscopic. Light sensitive. Air sensitive.

### 10.3. Possibility of hazardous reactions

**Hazardous Polymerization**  
**Hazardous Reactions**

Hazardous polymerization does not occur.  
No information available.

### 10.4. Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition. Do not subject to grinding/shock/friction. Exposure to light. Exposure to moist air or water. Incompatible products. Do not distill or allow to evaporate.

### 10.5. Incompatible materials

Bases. Strong oxidizing agents.

### 10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Hydrogen chloride gas.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Product Information

#### (a) acute toxicity;

**Oral**

Category 4

**Dermal**

Based on available data, the classification criteria are not met

**Inhalation**

Based on available data, the classification criteria are not met

#### Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Ethyl ether	1215 mg/kg (Rat)	20 mL/kg (Rabbit)	32000 ppm ( Rat ) 4 h

# SAFETY DATA SHEET

Hydrogen chloride, 1N solution in diethyl ether

Revision Date 09-Feb-2024

Hydrogen chloride	900 mg/kg ( Rabbit )	> 5010 mg/kg ( Rabbit )	LC50 = 4701 ppm (rat) 30 min (gas), LC50 = 588 ppm (4h) by extrapolation LC50 = 8.3 mg/L (rat ) 30 min (aerosols) (MMAD < 5µm)
-------------------	----------------------	-------------------------	---

- (b) skin corrosion/irritation;** Category 1 A
- (c) serious eye damage/irritation;** Category 1
- (d) respiratory or skin sensitization;**  
**Respiratory** Based on available data, the classification criteria are not met  
**Skin** Based on available data, the classification criteria are not met
- (e) germ cell mutagenicity;** Based on available data, the classification criteria are not met  
Mutagenic effects have occurred in humans
- (f) carcinogenicity;** Based on available data, the classification criteria are not met  
There are no known carcinogenic chemicals in this product
- (g) reproductive toxicity;** Based on available data, the classification criteria are not met
- (h) STOT-single exposure;** Category 3  
**Results / Target organs** Central nervous system (CNS).
- (i) STOT-repeated exposure;** Based on available data, the classification criteria are not met  
**Target Organs** None known.
- (j) aspiration hazard;** Based on available data, the classification criteria are not met
- Other Adverse Effects** The toxicological properties have not been fully investigated. See actual entry in RTECS for complete information
- Symptoms / effects,both acute and delayed** Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation.

## 11.2. Information on other hazards

**Endocrine Disrupting Properties** Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

**Ecotoxicity effects** Do not empty into drains.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Ethyl ether	LC50: > 10000 mg/L, 96h static (Lepomis macrochirus)	EC50 = 165 mg/L/24h	

# SAFETY DATA SHEET

Hydrogen chloride, 1N solution in diethyl ether

Revision Date 09-Feb-2024

	LC50: = 2560 mg/L, 96h flow-through (Pimephales promelas)		
--	---	--	--

Component	Microtox	M-Factor
Ethyl ether	EC50 = 5600 mg/L 15 min	

## 12.2. Persistence and degradability

### **Persistence**

Soluble in water, Persistence is unlikely, based on information available.

## 12.3. Bioaccumulative potential

Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Ethyl ether	0.82	No data available

## 12.4. Mobility in soil

The product is water soluble, and may spread in water systems Will likely be mobile in the environment due to its water solubility. Highly mobile in soils

## 12.5. Results of PBT and vPvB assessment

Substance is not considered persistent, bioaccumulative and toxic (PBT) / very persistent and very bioaccumulative (vPvB).

## 12.6. Endocrine disrupting properties

### **Endocrine Disruptor Information**

This product does not contain any known or suspected endocrine disruptors

## 12.7. Other adverse effects

### **Persistent Organic Pollutant Ozone Depletion Potential**

This product does not contain any known or suspected substance  
This product does not contain any known or suspected substance

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

#### **Waste from Residues/Unused Products**

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

#### **Contaminated Packaging**

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

#### **European Waste Catalogue (EWC)**

According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

#### **Other Information**

Waste codes should be assigned by the user based on the application for which the product was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Large amounts will affect pH and harm aquatic organisms.

## SECTION 14: TRANSPORT INFORMATION

### IMDG/IMO

#### 14.1. UN number

UN2924

#### 14.2. UN proper shipping name

Flammable liquid, corrosive, n.o.s.

# SAFETY DATA SHEET

Hydrogen chloride, 1N solution in diethyl ether

Revision Date 09-Feb-2024

**14.3. Transport hazard class(es)** 3  
**Subsidiary Hazard Class** 8  
**14.4. Packing group** I

## ADR

**14.1. UN number** UN2924  
**14.2. UN proper shipping name** Flammable liquid, corrosive, n.o.s.  
**14.3. Transport hazard class(es)** 3  
**Subsidiary Hazard Class** 8  
**14.4. Packing group** I

## IATA

**14.1. UN number** UN2924  
**14.2. UN proper shipping name** FLAMMABLE LIQUID, CORROSIVE, N.O.S.\*  
**14.3. Transport hazard class(es)** 3  
**Subsidiary Hazard Class** 8  
**14.4. Packing group** I

**14.5. Environmental hazards** No hazards identified  
**14.6. Special precautions for user** No special precautions required.  
**14.7. Maritime transport in bulk according to IMO instruments** Not applicable, packaged goods

## SECTION 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### International Inventories

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDSL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Ethyl ether	60-29-7	200-467-2	-	-	X	X	KE-27690	X	X
Hydrogen chloride	7647-01-0	231-595-7	-	-	X	X	KE-20189	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Ethyl ether	60-29-7	X	ACTIVE	X	-	X	X	X
Hydrogen chloride	7647-01-0	X	ACTIVE	X	-	X	X	X

**Legend:** X - Listed '-' - Not Listed      **KECL** - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

#### Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Ethyl ether	60-29-7	-	-	-
Hydrogen chloride	7647-01-0	-	Use restricted. See item 75. (see link for restriction details)	-

#### REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

# SAFETY DATA SHEET

Hydrogen chloride, 1N solution in diethyl ether

Revision Date 09-Feb-2024

## Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Ethyl ether	60-29-7	Not applicable	Not applicable
Hydrogen chloride	7647-01-0	25 tonne	250 tonne

## Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

## Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

## National Regulations

**UK** - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

## WGK Classification

Water endangering class = 1 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Ethyl ether	WGK1	
Hydrogen chloride	WGK1	

Component	France - INRS (Tables of occupational diseases)
Ethyl ether	Tableaux des maladies professionnelles (TMP) - RG 84

Component	Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)	Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)	Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure
Ethyl ether 60-29-7 ( 90-95 )		Group I	
Hydrogen chloride 7647-01-0 ( 5-10 )	Prohibited and Restricted Substances		

## 15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

## SECTION 16: OTHER INFORMATION

### Full text of H-Statements referred to under sections 2 and 3

H224 - Extremely flammable liquid and vapor

H302 - Harmful if swallowed

H314 - Causes severe skin burns and eye damage

H318 - Causes serious eye damage

H331 - Toxic if inhaled

# SAFETY DATA SHEET

Hydrogen chloride, 1N solution in diethyl ether

Revision Date 09-Feb-2024

H336 - May cause drowsiness or dizziness  
EUH019 - May form explosive peroxides  
EUH066 - Repeated exposure may cause skin dryness or cracking

## Legend

**CAS** - Chemical Abstracts Service

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**IECSC** - Chinese Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**ENCS** - Japanese Existing and New Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**NZIoC** - New Zealand Inventory of Chemicals

**WEL** - Workplace Exposure Limit

**ACGIH** - American Conference of Governmental Industrial Hygienists

**DNEL** - Derived No Effect Level

**RPE** - Respiratory Protective Equipment

**LC50** - Lethal Concentration 50%

**NOEC** - No Observed Effect Concentration

**PBT** - Persistent, Bioaccumulative, Toxic

**TWA** - Time Weighted Average

**IARC** - International Agency for Research on Cancer Predicted No Effect Concentration (PNEC)

**LD50** - Lethal Dose 50%

**EC50** - Effective Concentration 50%

**POW** - Partition coefficient Octanol:Water

**vPvB** - very Persistent, very Bioaccumulative

**ADR** - European Agreement Concerning the International Carriage of Dangerous Goods by Road

**IMO/IMDG** - International Maritime Organization/International Maritime Dangerous Goods Code

**OECD** - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

### Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

**ICAO/IATA** - International Civil Aviation Organization/International Air Transport Association

**MARPOL** - International Convention for the Prevention of Pollution from Ships

**ATE** - Acute Toxicity Estimate

**VOC** - (Volatile Organic Compound)

### Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

**Physical hazards** On basis of test data

**Health Hazards** Calculation method

**Environmental hazards** Calculation method

### Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

**Creation Date** 16-Nov-2010

**Revision Date** 09-Feb-2024

**Revision Summary** Not applicable.

**This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.**

### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**