

## SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

### 1.1. Product identifier

Product Description: n-Butyllithium, 1.6M in hexane  
Cat No. : L13559

Unique Formula Identifier (UFI) 43U1-93DM-YX02-TC5C

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended Use Laboratory chemicals.  
Uses advised against No Information available

### 1.3. Details of the supplier of the safety data sheet

#### Company

Avocado Research Chemicals Ltd.  
(Part of Thermo Fisher Scientific)  
Shore Road, Heysham  
Lancashire, LA3 2XY,  
United Kingdom  
Office Tel: +44 (0) 1524 850506  
Office Fax: +44 (0) 1524 850608

E-mail address [begel.sdsdesk@thermofisher.com](mailto:begel.sdsdesk@thermofisher.com)

### 1.4. Emergency telephone number

For information **US** call: 001-800-227-6701 / **Europe** call: +32 14 57 52 11  
Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99  
**CHEMTREC** Tel. No. **US**:001-800-424-9300 / **Europe**:001-703-527-3887

#### Poison Centre - Emergency information services

**Ireland** : National Poisons Information Centre (NPIC) -  
**01 809 2166** (8am-10pm, 7 days a week)  
**Malta** : +356 2395 2000  
**Cyprus** : +357 2240 5611

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the substance or mixture

#### GHS Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567

##### Physical hazards

Flammable liquids	Category 2 (H225)
Substances/mixtures which, in contact with water, emit flammable gases	Category 1 (H260)
Pyrophoric liquids	Category 1 (H250)

# SAFETY DATA SHEET

n-Butyllithium, 1.6M in hexane

Revision Date 16-May-2024

## Health hazards

Aspiration Toxicity	Category 1 (H304)
Skin Corrosion/Irritation	Category 1 B (H314)
Serious Eye Damage/Eye Irritation	Category 1 (H318)
Reproductive Toxicity	Category 2 (H361f)
Specific target organ toxicity - (single exposure)	Category 3 (H336)
Specific target organ toxicity - (repeated exposure)	Category 2 (H373)

## Environmental hazards

Chronic aquatic toxicity	Category 2 (H411)
--------------------------	-------------------

Full text of Hazard Statements: see section 16

## 2.2. Label elements



Signal Word

Danger

## Hazard Statements

- H225 - Highly flammable liquid and vapor
- H250 - Catches fire spontaneously if exposed to air
- H260 - In contact with water releases flammable gases which may ignite spontaneously
- H304 - May be fatal if swallowed and enters airways
- H314 - Causes severe skin burns and eye damage
- H336 - May cause drowsiness or dizziness
- H361f - Suspected of damaging fertility
- H373 - May cause damage to organs through prolonged or repeated exposure
- H411 - Toxic to aquatic life with long lasting effects
- EUH014 - Reacts violently with water

## Precautionary Statements

- P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- P280 - Wear protective gloves/protective clothing/eye protection/face protection
- P302 + P335 + P334 - IF ON SKIN: Brush off loose particles from skin. Immerse in cool water
- P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
- P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- P310 - Immediately call a POISON CENTER or doctor/physician

## 2.3. Other hazards

This product does not contain any known or suspected endocrine disruptors

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

# SAFETY DATA SHEET

n-Butyllithium, 1.6M in hexane

Revision Date 16-May-2024

## 3.2. Mixtures

Component	CAS No	EC No	Weight %	GHS Classification - According to GB-CLP Regulations UK SI 2019/720 and UK SI 2020/1567
Hexane	110-54-3	EEC No. 203-777-6	85	Flam. Liq. 2 (H225) Asp. Tox. 1 (H304) Skin Irrit. 2 (H315) STOT SE 3 (H336) Repr. 2 (H361f) STOT RE 2 (H373) Aquatic Chronic 2 (H411)
Butyl lithium	109-72-8	203-698-7	15	Pyr. Liq. 1 (H250) Water react. 1 (H260) Skin Corr. 1B (H314) Eye Dam. 1 (H318) (EUH014)

Component	Specific concentration limits (SCL's)	M-Factor	Component notes
Hexane	STOT RE 2 (H373) :: C>=5%	-	-

Components	Reach Registration Number
Butyl lithium	01-2119494906-21

Full text of Hazard Statements: see section 16

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of first aid measures

<b>General Advice</b>	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
<b>Eye Contact</b>	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Immediate medical attention is required.
<b>Skin Contact</b>	Wash off immediately with plenty of water for at least 15 minutes. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Call a physician immediately.
<b>Ingestion</b>	Do NOT induce vomiting. Clean mouth with water. Never give anything by mouth to an unconscious person. Call a physician immediately. Call a physician or poison control center immediately. If vomiting occurs naturally, have victim lean forward.
<b>Inhalation</b>	If not breathing, give artificial respiration. Remove from exposure, lie down. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician immediately. Risk of serious damage to the lungs (by aspiration).
<b>Self-Protection of the First Aider</b>	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

### 4.2. Most important symptoms and effects, both acute and delayed

Difficulty in breathing. Causes burns by all exposure routes. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting; Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated:

# SAFETY DATA SHEET

n-Butyllithium, 1.6M in hexane

Revision Date 16-May-2024

Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation

## 4.3. Indication of any immediate medical attention and special treatment needed

**Notes to Physician** Treat symptomatically. Symptoms may be delayed.

## SECTION 5: FIREFIGHTING MEASURES

### 5.1. Extinguishing media

#### **Suitable Extinguishing Media**

Dry chemical. Limestone powder. Dry sand. approved class D extinguishers. Water mist may be used to cool closed containers.

#### **Extinguishing media which must not be used for safety reasons**

Water. Carbon dioxide (CO<sub>2</sub>). Foam.

### 5.2. Special hazards arising from the substance or mixture

Thermal decomposition can lead to release of irritating gases and vapors. The product causes burns of eyes, skin and mucous membranes. Reacts violently with water. Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

#### **Hazardous Combustion Products**

Carbon monoxide (CO), Carbon dioxide (CO<sub>2</sub>), Thermal decomposition can lead to release of irritating gases and vapors, Butane.

### 5.3. Advice for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Thermal decomposition can lead to release of irritating gases and vapors.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

Use personal protective equipment as required. Ensure adequate ventilation. Evacuate personnel to safe areas. Keep people away from and upwind of spill/leak. Remove all sources of ignition. Take precautionary measures against static discharges.

### 6.2. Environmental precautions

Do not flush into surface water or sanitary sewer system.

### 6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Do not expose spill to water. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

### 6.4. Reference to other sections

Refer to protective measures listed in Sections 8 and 13.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for safe handling

Wear personal protective equipment/face protection. Do not get in eyes, on skin, or on clothing. Use only under a chemical fume

# SAFETY DATA SHEET

n-Butyllithium, 1.6M in hexane

Revision Date 16-May-2024

hood. Do not breathe mist/vapors/spray. Do not ingest. If swallowed then seek immediate medical assistance. Do not allow contact with water. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

## Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and after work.

## 7.2. Conditions for safe storage, including any incompatibilities

Keep away from heat, sparks and flame. Keep under nitrogen. Keep refrigerated. Flammables area. Corrosives area. Keep away from water or moist air. Keep container tightly closed in a dry and well-ventilated place.

**Technical Rules for Hazardous Substances (TRGS) 510** Class 4.2  
**Storage Class (LGK) (Germany)**

## 7.3. Specific end use(s)

Use in laboratories

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

#### Exposure limits

List source(s): **EU** - Commission Directive (EU) 2019/1831 of 24 October 2019 establishing a fifth list of indicative occupational exposure limit values pursuant to Council Directive 98/24/EC and amending Commission Directive 2000/39/EC **UK** - EH40/2005 Work Exposure Limits, Fourth edition. Published 2020. **IRE** - 2021 Code of Practice for the Chemical Agents Regulations, Schedule 1. Published by the Health and Safety Authority

Component	The United Kingdom	European Union	Ireland
Hexane	TWA: 72 mg/m <sup>3</sup> TWA: 20 ppm STEL: 60 ppm STEL: 216 mg/m <sup>3</sup>	TWA: 20 ppm (8hr) TWA: 72 mg/m <sup>3</sup> (8hr)	TWA: 20 ppm 8 hr. TWA: 72 mg/m <sup>3</sup> 8 hr. STEL: 60 ppm 15 min STEL: 216 mg/m <sup>3</sup> 15 min Skin

#### Biological limit values

List source(s):

#### Derived No Effect Level (DNEL) / Derived Minimum Effect Level (DMEL)

See table for values

Component	Acute effects local (Dermal)	Acute effects systemic (Dermal)	Chronic effects local (Dermal)	Chronic effects systemic (Dermal)
Hexane 110-54-3 ( 85 )				DNEL = 11mg/kg bw/day

Component	Acute effects local (Inhalation)	Acute effects systemic (Inhalation)	Chronic effects local (Inhalation)	Chronic effects systemic (Inhalation)
Hexane 110-54-3 ( 85 )				DNEL = 75mg/m <sup>3</sup>

# SAFETY DATA SHEET

n-Butyllithium, 1.6M in hexane

Revision Date 16-May-2024

## Predicted No Effect Concentration (PNEC)

No information available.

## 8.2. Exposure controls

### Engineering Measures

Use only under a chemical fume hood. Use explosion-proof electrical/ventilating/lighting equipment. Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas.

Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

### Personal protective equipment

**Eye Protection** Goggles (European standard - EN 166)

**Hand Protection** Protective gloves

Glove material	Breakthrough time	Glove thickness	EU standard	Glove comments
Nitrile rubber	See manufacturers	-	EN 374	(minimum requirement)
Viton (R)	recommendations			

**Skin and body protection** Long sleeved clothing.

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatibility, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

**Respiratory Protection** When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

**Large scale/emergency use** Use a NIOSH/MSHA or European Standard EN 136 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced  
**Recommended Filter type:** low boiling organic solvent Type AX Brown conforming to EN371

**Small scale/Laboratory use** Use a NIOSH/MSHA or European Standard EN 149:2001 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.  
**Recommended half mask:-** Valve filtering: EN405; or; Half mask: EN140; plus filter, EN 141  
When RPE is used a face piece Fit Test should be conducted

**Environmental exposure controls** Prevent product from entering drains. Do not allow material to contaminate ground water system.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on basic physical and chemical properties

**Physical State** Liquid

**Appearance** Yellow

# SAFETY DATA SHEET

n-Butyllithium, 1.6M in hexane

Revision Date 16-May-2024

<b>Odor</b>	Petroleum distillates	
<b>Odor Threshold</b>	No data available	
<b>Melting Point/Range</b>	-95 °C / -139 °F	
<b>Softening Point</b>	No data available	
<b>Boiling Point/Range</b>	60 - 80 °C / 140 - 176 °F	@ 760 mmHg
<b>Flammability (liquid)</b>	Highly flammable	On basis of test data
<b>Flammability (solid,gas)</b>	Not applicable	Liquid
<b>Explosion Limits</b>	<b>Lower</b> 1.2 Vol% <b>Upper</b> 7.8 Vol%	
<b>Flash Point</b>	-21 °C / -5.8 °F	<b>Method -</b> (based on components)
<b>Autoignition Temperature</b>	240 °C / 464 °F	
<b>Decomposition Temperature</b>	No data available	
<b>pH</b>	No information available	
<b>Viscosity</b>	No data available	
<b>Water Solubility</b>	Reacts with water	
<b>Solubility in other solvents</b>	No information available	
<b>Partition Coefficient (n-octanol/water)</b>		
<b>Component</b>	<b>log Pow</b>	
Hexane	4.11	
<b>Vapor Pressure</b>	160 mbar @ 20 °C	
<b>Density / Specific Gravity</b>	0.680	
<b>Bulk Density</b>	Not applicable	Liquid
<b>Vapor Density</b>	No data available	(Air = 1.0)
<b>Particle characteristics</b>	Not applicable (liquid)	

## 9.2. Other information

<b>Explosive Properties</b>	Vapors may form explosive mixtures with air
<b>Substances/mixtures which, in contact with water, emit flammable gases</b>	Emitted gas ignites spontaneously Gas(es) = Butane

## SECTION 10: STABILITY AND REACTIVITY

### 10.1. Reactivity

Yes

### 10.2. Chemical stability

Water reactive. Reacts violently with water. Air sensitive.

### 10.3. Possibility of hazardous reactions

<b>Hazardous Polymerization</b>	Hazardous polymerization does not occur.
<b>Hazardous Reactions</b>	Reacts violently with water.

### 10.4. Conditions to avoid

Incompatible products. Heat, flames and sparks. Exposure to moist air or water. Exposure to air. Exposure to moisture. Keep away from open flames, hot surfaces and sources of ignition.

### 10.5. Incompatible materials

Strong oxidizing agents. Halogens.

### 10.6. Hazardous decomposition products

Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Thermal decomposition can lead to release of irritating gases and vapors. Butane.

## SECTION 11: TOXICOLOGICAL INFORMATION

# SAFETY DATA SHEET

n-Butyllithium, 1.6M in hexane

Revision Date 16-May-2024

## 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

### Product Information

#### (a) acute toxicity;

Oral

Based on available data, the classification criteria are not met

Dermal

Based on available data, the classification criteria are not met

Inhalation

Based on available data, the classification criteria are not met

### Toxicology data for the components

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Hexane	LD50 = 25 g/kg ( Rat )	LD50 = 3000 mg/kg ( Rabbit )	LC50 = 48000 ppm ( Rat ) 4 h

(b) skin corrosion/irritation; Category 1 B

(c) serious eye damage/irritation; Category 1

#### (d) respiratory or skin sensitization;

Respiratory

No data available

Skin

No data available

(e) germ cell mutagenicity; No data available

(f) carcinogenicity; No data available

There are no known carcinogenic chemicals in this product

#### (g) reproductive toxicity; Reproductive Effects

Category 2  
Possible risk of impaired fertility.

#### (h) STOT-single exposure;

Category 3

Results / Target organs

Central nervous system (CNS).

#### (i) STOT-repeated exposure;

Category 2

Target Organs

Eyes, Respiratory system, Skin, Gastrointestinal tract (GI), Central nervous system (CNS), Liver, Peripheral Nervous System (PNS).

(j) aspiration hazard; Category 1

#### Other Adverse Effects

Tumorigenic effects have been reported in experimental animals.

#### Symptoms / effects, both acute and delayed

Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Product is a corrosive material. Use of gastric lavage or emesis is contraindicated. Possible perforation of stomach or esophagus should be investigated. Ingestion causes severe swelling, severe damage to the delicate tissue and danger of perforation.

## 11.2. Information on other hazards



# SAFETY DATA SHEET

n-Butyllithium, 1.6M in hexane

Revision Date 16-May-2024

**Endocrine Disrupting Properties** Assess endocrine disrupting properties for human health. This product does not contain any known or suspected endocrine disruptors.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

#### Ecotoxicity effects

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following substances which are hazardous for the environment.

Component	Freshwater Fish	Water Flea	Freshwater Algae
Hexane	LC50: 2.1 - 2.98 mg/L, 96h flow-through (Pimephales promelas)	EC50: 3.87 mg/L/48h	

### 12.2. Persistence and degradability

#### Persistence

Persistence is unlikely, based on information available.

#### Degradation in sewage treatment plant

Contains substances known to be hazardous to the environment or not degradable in waste water treatment plants.

### 12.3. Bioaccumulative potential

Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Hexane	4.11	No data available

### 12.4. Mobility in soil

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. Will likely be mobile in the environment due to its volatility. Disperses rapidly in air.

### 12.5. Results of PBT and vPvB assessment

No data available for assessment.

### 12.6. Endocrine disrupting properties

#### Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

### 12.7. Other adverse effects

#### Persistent Organic Pollutant Ozone Depletion Potential

This product does not contain any known or suspected substance

This product does not contain any known or suspected substance

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

#### Waste from Residues/Unused Products

Waste is classified as hazardous. Dispose of in accordance with the European Directives on waste and hazardous waste. Dispose of in accordance with local regulations.

#### Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

# SAFETY DATA SHEET

n-Butyllithium, 1.6M in hexane

Revision Date 16-May-2024

**European Waste Catalogue (EWC)** According to the European Waste Catalog, Waste Codes are not product specific, but application specific.

**Other Information** Do not flush to sewer. Waste codes should be assigned by the user based on the application for which the product was used. Can be landfilled or incinerated, when in compliance with local regulations. Do not empty into drains. Large amounts will affect pH and harm aquatic organisms. Do not let this chemical enter the environment.

## SECTION 14: TRANSPORT INFORMATION

### IMDG/IMO

**14.1. UN number** UN3394  
**14.2. UN proper shipping name** ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE  
**Technical Shipping Name** Hexane, Butyl lithium  
**14.3. Transport hazard class(es)** 4.2  
**Subsidiary Hazard Class** 4.3  
**14.4. Packing group** I

### ADR

**14.1. UN number** UN3394  
**14.2. UN proper shipping name** ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE  
**Technical Shipping Name** Hexane, Butyl lithium  
**14.3. Transport hazard class(es)** 4.2  
**Subsidiary Hazard Class** 4.3  
**14.4. Packing group** I

### IATA

FORBIDDEN FOR IATA TRANSPORT

**14.1. UN number** UN3394  
**14.2. UN proper shipping name** ORGANOMETALLIC SUBSTANCE, LIQUID, PYROPHORIC, WATER-REACTIVE  
**Technical Shipping Name** Hexane, Butyl lithium  
**14.3. Transport hazard class(es)** 4.2  
**Subsidiary Hazard Class** 4.3  
**14.4. Packing group** I

**14.5. Environmental hazards** Dangerous for the environment  
Product is a marine pollutant according to the criteria set by IMDG/IMO

**14.6. Special precautions for user** No special precautions required.

**14.7. Maritime transport in bulk according to IMO instruments** Not applicable, packaged goods

## SECTION 15: REGULATORY INFORMATION

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **International Inventories**

Europe (EINECS/ELINCS/NLP), China (IECSC), Taiwan (TCSI), Korea (KECL), Japan (ENCS), Japan (ISHL), Canada (DSL/NDL), Australia (AICS), New Zealand (NZIoC), Philippines (PICCS). US EPA (TSCA) - Toxic Substances Control Act, (40 CFR Part 710)

# SAFETY DATA SHEET

n-Butyllithium, 1.6M in hexane

Revision Date 16-May-2024

Component	CAS No	EINECS	ELINCS	NLP	IECSC	TCSI	KECL	ENCS	ISHL
Hexane	110-54-3	203-777-6	438-390-3	-	X	X	KE-18626	X	X
Butyl lithium	109-72-8	203-698-7	-	-	X	X	KE-04320	X	X

Component	CAS No	TSCA	TSCA Inventory notification - Active-Inactive	DSL	NDSL	AICS	NZIoC	PICCS
Hexane	110-54-3	X	ACTIVE	X	-	X	X	X
Butyl lithium	109-72-8	X	ACTIVE	X	-	X	X	X

**Legend:** X - Listed '-' - Not Listed      **KECL** - NIER number or KE number (<http://ncis.nier.go.kr/en/main.do>)

## Authorisation/Restrictions according to EU REACH

Component	CAS No	REACH (1907/2006) - Annex XIV - Substances Subject to Authorization	REACH (1907/2006) - Annex XVII - Restrictions on Certain Dangerous Substances	REACH Regulation (EC 1907/2006) article 59 - Candidate List of Substances of Very High Concern (SVHC)
Hexane	110-54-3	-	Use restricted. See item 75. (see link for restriction details)	-
Butyl lithium	109-72-8	-	-	-

### REACH links

<https://echa.europa.eu/substances-restricted-under-reach>

## Seveso III Directive (2012/18/EC)

Component	CAS No	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Major Accident Notification	Seveso III Directive (2012/18/EC) - Qualifying Quantities for Safety Report Requirements
Hexane	110-54-3	Not applicable	Not applicable
Butyl lithium	109-72-8	Not applicable	Not applicable

## Regulation (EC) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of dangerous chemicals

Not applicable

## Contains component(s) that meet a 'definition' of per & poly fluoroalkyl substance (PFAS)?

Not applicable

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work .

Take note of Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values

Take note of Directive 94/33/EC on the protection of young people at work

Take note of Dir 92/85/EC on the protection of pregnant and breastfeeding women at work

## National Regulations

**UK** - Take note of Control of Substances Hazardous to Health Regulations (COSHH) 2002 and 2005 Amendment

## WGK Classification

Water endangering class = 2 (self classification)

Component	Germany - Water Classification (AwSV)	Germany - TA-Luft Class
Hexane	WGK2	
Butyl lithium	WGK1	

# SAFETY DATA SHEET

n-Butyllithium, 1.6M in hexane

Revision Date 16-May-2024

<b>Component</b>	<b>France - INRS (Tables of occupational diseases)</b>
Hexane	Tableaux des maladies professionnelles (TMP) - RG 59, RG 84

<b>Component</b>	<b>Switzerland - Ordinance on the Reduction of Risk from handling of hazardous substances preparation (SR 814.81)</b>	<b>Switzerland - Ordinance on Incentive Taxes on Volatile Organic Compounds (OVOC)</b>	<b>Switzerland - Ordinance of the Rotterdam Convention on the Prior Informed Consent Procedure</b>
Hexane 110-54-3 ( 85 )	Prohibited and Restricted Substances	Group I	

## 15.2. Chemical safety assessment

Chemical Safety Assessment/Reports (CSA/CSR) are not required for mixtures

## SECTION 16: OTHER INFORMATION

### Full text of H-Statements referred to under sections 2 and 3

H225 - Highly flammable liquid and vapor  
H250 - Catches fire spontaneously if exposed to air  
H260 - In contact with water releases flammable gases which may ignite spontaneously  
H304 - May be fatal if swallowed and enters airways  
H314 - Causes severe skin burns and eye damage  
H315 - Causes skin irritation  
H318 - Causes serious eye damage  
H336 - May cause drowsiness or dizziness  
H361f - Suspected of damaging fertility  
H411 - Toxic to aquatic life with long lasting effects  
EUH014 - Reacts violently with water

### Legend

**CAS** - Chemical Abstracts Service

**EINECS/ELINCS** - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances

**PICCS** - Philippines Inventory of Chemicals and Chemical Substances

**IECSC** - Chinese Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

**WEL** - Workplace Exposure Limit

**ACGIH** - American Conference of Governmental Industrial Hygienists

**DNEL** - Derived No Effect Level

**RPE** - Respiratory Protective Equipment

**LC50** - Lethal Concentration 50%

**NOEC** - No Observed Effect Concentration

**PBT** - Persistent, Bioaccumulative, Toxic

**TSCA** - United States Toxic Substances Control Act Section 8(b) Inventory

**DSL/NDSL** - Canadian Domestic Substances List/Non-Domestic Substances List

**ENCS** - Japanese Existing and New Chemical Substances

**AICS** - Australian Inventory of Chemical Substances

**NZIoC** - New Zealand Inventory of Chemicals

**TWA** - Time Weighted Average

**IARC** - International Agency for Research on Cancer Predicted No Effect Concentration (PNEC)

**LD50** - Lethal Dose 50%

**EC50** - Effective Concentration 50%

**POW** - Partition coefficient Octanol:Water

**vPvB** - very Persistent, very Bioaccumulative

**ADR** - European Agreement Concerning the International Carriage of Dangerous Goods by Road

**IMO/MDG** - International Maritime Organization/International Maritime Dangerous Goods Code

**OECD** - Organisation for Economic Co-operation and Development

**BCF** - Bioconcentration factor

### Key literature references and sources for data

<https://echa.europa.eu/information-on-chemicals>

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

**ICAO/IATA** - International Civil Aviation Organization/International Air Transport Association

**MARPOL** - International Convention for the Prevention of Pollution from Ships

**ATE** - Acute Toxicity Estimate

**VOC** - (Volatile Organic Compound)

# SAFETY DATA SHEET

n-Butyllithium, 1.6M in hexane

Revision Date 16-May-2024

---

**Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:**

<b>Physical hazards</b>	On basis of test data
<b>Health Hazards</b>	Calculation method
<b>Environmental hazards</b>	Calculation method

## Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Fire prevention and fighting, identifying hazards and risks, static electricity, explosive atmospheres posed by vapours and dusts.

Chemical incident response training.

<b>Prepared By</b>	Health, Safety and Environmental Department
<b>Creation Date</b>	18-Oct-2010
<b>Revision Date</b>	16-May-2024
<b>Revision Summary</b>	New emergency telephone response service provider.

**This safety data sheet complies with Regulation UK SI 2019/758 and UK SI 2020/1577 as amended.**

## Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

**End of Safety Data Sheet**